February 2014 AMVs vs Radiosonde (0000 & 1200 UTC)

Northern hemisphere	No of Colloca tion	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	252	5.6	6.0	1.7	3.7	23.4	1.8	10.1	8.4
Mid level CMV	1237	8.0	9.2	4.3	5.8	16.2	0.0	18.7	18.7
High level CMV	769	8.9	10.2	4.7	6.7	12.5	-1.8	24.6	26.4
High level WVWV	1563	8.8	8.8	5.0	6.1	14.8	-0.8	23.5	24.3

Tropics	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	152	5.3	5.5	1.1	3.6	26.8	2.3	8.4	6.1
Mid level CMV	304	6.3	6.6	1.4	4.4	22.9	3.3	11.7	8.3
High level CMV	3939	6.8	7.8	3.7	5.4	19.8	1.7	14.8	13.0
High level WVWV	3964	7.2	8.1	3.7	4.7	20.6	1.7	14.9	13.2

Southern hemisphere	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	6	5.5	5.5	0.0	4.1	21.1	4.1	10.8	6.6
Mid level CMV	5	5.0	5.0	0.2	3.5	17.3	2.8	9.2	6.4
High level CMV	39	5.3	5.5	0.7	3.1	25.7	1.9	9.7	7.7
High level WVWV	95	7.1	7.3	1.1	4.6	25.9	2.2	11.2	9.0

Global	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	410	5.3	5.8	1.9	3.6	24.3	1.9	9.3	7.5
Mid level CMV	1583	7.8	9.0	4.2	5.6	17.3	0.7	17.8	17.1
High level CMV	4747	7.2	8.4	4.2	4.8	18.4	1.1	16.8	15.7
High level WVWV	5622	7.7	9.0	4.6	5.1	19.0	0.9	17.6	16.6

MVD: Mean vector differenceRMSVD: Root mean square vector differenceSD: Standard DeviationMean Speed Dif (ABS): Absolute mean wind speed differenceMean Dir Dif (ABS): Absolute mean wind direction difference

High level: 100-400hPa Mid level: 401-700hPa Low level: 701-975hPa

MVD, RMSVD, SD, Mean Speed Dif, Mean Speed AMV, Mean Speed RS are in ms⁻¹, Mean Dir Dif is in degree.

Collocation Criteria:

- All AMVs within 150km of each radiosonde location and pressure difference ±20hPa are considered for validation.
- Collocation pairs with speed difference greater than 30ms⁻¹ and direction difference greater than 60° are screened out.
- Quality indicator is not used for the current validation.