

# November 2014

## AMVs vs Radiosonde (0000 & 1200 UTC)

Northern hemisphere	No of Colloca tion	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Mean Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	316	5.9	6.3	1.8	4.2	25.1	2.0	10.1	8.1
Mid level CMV	1318	7.6	8.9	4.3	6.0	15.4	1.7	16.8	15.1
High level CMV	1219	8.0	9.1	4.2	5.8	14.0	-1.0	20.4	21.3
High level WVWV	2102	8.4	8.4	5.1	6.1	15.1	-0.2	21.1	21.3

  

Tropics	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Mean Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	142	4.4	4.6	1.0	3.3	20.7	2.3	8.8	6.5
Mid level CMV	184	5.5	5.8	1.3	4.3	24.7	3.6	9.6	5.9
High level CMV	4242	5.1	5.7	2.6	3.2	20.3	0.4	10.1	9.7
High level WVWV	3248	4.8	5.5	2.6	3.1	19.4	0.7	10.2	9.6

  

Southern hemisphere	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Mean Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	3	10.1	10.1	0.1	8.2	44.9	5.2	14.6	9.4
Mid level CMV	3	9.6	9.7	2.9	21.5	32.9	8.5	30.3	21.8
High level CMV	32	9.1	9.3	2.0	11.9	16.0	5.1	31.2	26.1
High level WVWV	85	12.2	12.6	1.7	8.9	26.1	3.5	19.1	15.6

  

Global	No of Collocation	MVD	RMSVD	SD	Mean Speed Dif (ABS)	Mean Dir Dif (ABS)	Mean Bias	Mean Speed AMV	Mean Speed RS
Low level CMV	461	5.3	5.8	2.2	3.6	24.3	1.9	9.4	7.5
Mid level CMV	1505	7.2	8.6	4.4	5.7	16.0	1.8	15.9	14.1
High level CMV	5493	5.7	6.8	3.5	3.8	18.6	0.1	12.6	12.5
High level WVWV	5435	6.3	7.7	4.3	4.3	17.5	0.5	14.8	14.2

MVD: Mean vector difference

RMSVD: Root mean square vector difference

SD: Standard Deviation

Mean Speed Dif (ABS): Absolute mean wind speed difference

Mean Dir Dif (ABS): Absolute mean wind direction difference

High level: 100-400hPa

Mid level: 401-700hPa

Low level: 701-975hPa

**MVD, RMSVD, SD, Mean Speed Dif, Mean Speed AMV, Mean Speed RS are in  $\text{ms}^{-1}$ , Mean Dir Dif is in degree.**

**Collocation Criteria:**

- All AMVs within 150km of each radiosonde location and pressure difference  $\pm 20\text{hPa}$  are considered for validation.
- Collocation pairs with speed difference greater than  $30\text{ms}^{-1}$  and direction difference greater than  $60^\circ$  are screened out.
- Quality indicator is not used for the current validation.